Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of LaborOccupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List) POOL INSTANT S	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.								
Section I – General Information									
Manufacturer's Name:	Telephone Number for Information:								
QUALCO, INC. Address (Number, Street, City, State and ZIP Code)	973-473-1222 Emergency Telephone Number								
225 Passaic Street	(973) 473-1222 or (CHEMTREC) 1-800-424-9300								
Passaic, NJ 07055	Date Prepared								
,		JUNE 2009	non (ontional)						
		Signature of Prepa	rer (optional)						
Section II – Hazardous Ingredients/Identity Information									
Hazardous Components (Specific Chemical Identity: Con	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)					
Sodium Dichloro-s-triazinetrione Dihydrai	Not Est	1 PPM as							
(CAS #51580-86-0)(Sodium dichloroisoc	Chlorine								
Hydrate)		Other Limits	3						
,,		Oral LD 50	(Rats)	550-1600 mg/kg					
		Inhal. LC50	>200 mg/liter						
		Dermal LD5	(Rabbit):	>5,000 mg/kg					
Not Classified by D.O.T. Material corrosive									
Material considered a severe eye & skin irritant									
EPA Registered Pesticide 3525-107									
NFPA Class I Oxidizer									
Section III - Physical/Chemical Cha	racteristics								
Boiling Point	N/A	Specific Gravity (H	$I_2O = 1$) Bulk Density		< 1				
Vapor Pressure (mm Hg.)	N/A	Melting Point – Decomposes @			350°F				
Vapor Density (AIR = 1)	Vapor Density (AIR = 1) N/A			Evaporation Rate (Butyl Acetate = 1)					
Solubility in Water Moderate	pH: (1% Solution): 5.8 to 7.0								
Appearance and Odor White Free Flowing Granular/Powder with a chlorinous odor									
Section IV – Fire and Explosion Ha		vitir a critorii loa	3 0001						
	mmable Limits	LEL		UEL					
No.	on-Flammable	N.	/A	N/A					
Extinguished Media Deluge with water.									
Special Fire Fighting Procedures:									
Use NIOSH certified gas mask with canister for chlorine. If possible, remove container to open air and flood with									
water. Damp or decomposing material may be shock sensitive. Rap container sharply with a pole from a distant, protected position prior to handling.									
Unusual Fire and Explosion Hazards									
Decomposition products: Chlorine, cyanogens chloride, carbon dioxide, ammonia, nitrogen trichloride.									

Pool Trol Instant Shock								
Section V -	- Reactivity Data							
Stability	Unstable		Conditions to Avoid: Open storage, excessive heat, moist air, combinations with oxidizers or oxidizable materials.					
	Stable	X	<u> </u>		es at room temperature.			
Incompatibility (M	laterials to Avoid) Nitroge	en con						
Incompatibility (Materials to Avoid) Nitrogen compounds – Ammonia, Amines, Ammonium compounds, Reducing Agents, Oxidizable or Combustible organics, Strong Oxidizers, Acids, Alkali.								
		hlorine			ogen trichloride, Ammonia, Carbon dioxide.			
Hazardous Polymerization	May Occur		Conditions to Avoid	l N/A				
· o.yon_auto	Will Not Occur	X						
Section VI	 Health Hazard D 	Data						
Route(s) of Entry		In	halation? Yes	Skin? Yes	Ingestion? Yes			
Health Hazards (/	Acute and Chronic) Acute	e: Eye	: Extreme irritar	nt, cornea	damage, Inhalation: Extreme irritant.			
	damage, Lung dam							
	<u> </u>							
Carcinogenicity N/A		N	TP? N/A	IARC Monographs N/A	? OSHA Regulated? N/A			
Signs and Symptoms of Exposure: Eye & Skin: Irritation, burning, redness, eye tearing. Inhalation: Coughing, irritation to nose, throat, and mouth; headache, dizziness.								
	I discomfort, naus							
Medical Condition			<u> </u>					
Generally Aggravated by Exposure Persons with pre-existing eye, skin and respiratory disorders may be susceptible to								
	due to irritant nature							
	•		•		water. Call physician immediately.			
	ove to fresh air. Cal							
•			wed by olive oil.	Induce vo	omiting if large amount has been ingested. Call			
	d follow all instructio							
Section VII	 Precautions for 	r Safe	e Handling an	d Use				
	n in Case Material is Releas							
with water ar					jor spills or bulk decomposition should be deluged as dirt or absorbent pads) until reaction has been			
quenched.								
	into fresh water, stre							
Waste Disposal Method Spilled or wet material should be dissolved in water and dechlorinated with a reducing agent. (Hydrogen peroxide, sodium nitrate, sodium thiosulfate).								
Dispose of material as per all local, state and federal regulations.								
Precautions To Be Taken In Handling And Storing								
Store in a cool, dry, well-ventilated area away from combustibles and reactive materials. Keep container tightly								
closed when not in use. Do not reuse container. Wear proper protective gear when handling to minimize contact with product.								
Other Precautions								
Keep away from children. Use product only as directed. Handle with care.								
Section VIII - Control Measures								
Respiratory Protection (Specify Type) Wear NIOSH certified gas mask with canister for chlorine if above permissible limits.								
Ventillation	Local Exhaust Adequa	ite			special If permissible limits are exceeded, additional ventilation/exhaust is necessary.			
	Mechanical (General)				Other			
Protective Gloves	·			Protection Do not wear contact lenses. Use gas tight emical goggles.				
Other Protective Clothing or Equipment Eye wash & safety shower in work/storage areas. Wear full cover clothing as								
necessary to minimize contact with product. Work/Hygienic Practices Remove contaminated clothing and launder before reuse. Wash well after use and observe								
	quod, personal hygiene.							

Addendum - Page 1

Handling & Storage of: Sodium Dichloroisocyanuric Acid

Keep Out Of Reach Of Children

Danger: Do not mix with anything but water. Replace container cover after use.

Strong Oxidizer: Contact with other material may cause fire or explosion.

Keep from contact with clothing and other combustible materials. Do not store near combustible materials. Remove and wash contaminated clothing promptly and before reuse.

- 1. Do not smoke when handling material.
- 2. While product by itself is not a combustible material, it must not be mixed or contaminated with any foreign materials such as: household products, soap products, paint products, solvents, acids, pool chemicals, garbage, vinegar, beverages, oils, pine oil, dirty rags, etc.
 Contamination or mixing with these type of items may result in fire or explosion, and the fire can be of great intensity. NOTE: Dampened material and/or excessive moisture to product can also result in fire or reaction.
- 3. Prevent any burning material, such as a lighted cigarette from falling into any container of product.
- 4. If fire occurs, wear proper protective gear. Drench with water and cool the surrounding drums and area with water.
- 5. Use only a clean, dry cup or measuring device to remove product from container. Any contamination or foreign matter on the cup/measuring device may result in fire. Always keep material in original container to avoid contamination.
- 6. Keep in a cool, dry, well ventilated area which is clean. Keep in original container. Always replace container cover. Do not store in any other container.
- 7. Handle material with care. Do not drop, roll or skid. Keep upright.
- 8. Dispose of spilled material by dissolving in large amounts of water. (Always add SMALL amounts of product to LARGE amounts of water. Let stand after dissolving and check for PPM (parts per million) available chlorine using a pool water test kit. If regulations and/or your sewer authority permit discharge of material (usually less than 1 ppm available chlorine, then material can be discharged to sewer. Do not discharge without prior approval of authority.
- 9. Do not reuse empty container. Wash thoroughly with plenty of water and discard to trash.
- 10. Product may produce severe chemical burns. Do not allow contact with eyes, skin, mucous membranes or clothing. **Harmful or fatal if swallowed.**

SODIUM DICHLOROISOCYANURIC ACID

FIRST AID: EXTERNAL: Flood skin or eyes with copious amounts of water for 15

minutes. For eyes, call physician immediately. If skin irritation persists, get

medical attention.

INTERNAL: If conscious, promptly drink large quantities of water. Do not induce vomiting, (unless instructed by physician). Get immediate medical

attention.

INHALATION: Move victim to fresh air. Call physician. Aid breathing, if

necessary.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

NOTE: Use extreme caution in handling spilled material. Contamination with organic or combustible material may cause fire or violent decomposition.

If fire or composition occurs in area of spill, immediately dose with large amounts of water. Otherwise, sweep up all visible material using a CLEAN, DRY shovel or broom, and dissolve in large amounts of water before disposing of wastes.

Dispose of waste materials as outlined below.

Wear proper protective gear: Coveralls, splash apron, goggles, impervious gloves, NIOSH certified gas mask with canister for chlorine.

WASTE DISPOSAL METHOD: Spilled material that has been swept up and dissolved in large

amounts of water should be used immediately in the normal application for which the product is being consumed. If this is not

possible, CAREFULLY neutralize material as follows:

This procedure can only be used for small spills of 10 pounds or less, and only if regulation permits disposal of solutions containing 1 ppm (or less) available chlorine to the sewer. DO NOT discharge to sewer without prior approval of authority.

Place clean drum (about 55 gallon size) outdoors away from spill. Fill drum with tap water (3/4 full). Add spilled chemical (10 pounds maximum). Allow to dissolve in solution and let stand until available chlorine is less than 1 ppm (as determined by a pool water test kit). Then flush to sewer if permitted.

NOTE: Only properly neutralized material should be flushed to sewer. Un-neutralized material can cause environmental damage to receiving water, or can interfere with treatment plant operations.

STORAGE AND HANDLING PRECAUTIONS:

- Do not get in eyes, on skin or on clothing.
- Keep in original container in cool, dry, well ventilated area.
- Keep container tightly closed when not in use.
- Keep away from heat, sparks, flame, fire and sources of ignition.
- Use only a clean, dry scoop/measuring aid each time material is taken from container.
- Fire can result if material is contaminated with acids, combustibles, organic materials and dirt.
- Wear protective gear required when handling. Wash well after handling.
- Do not reuse empty container. Rinse well with plenty of water to dissolve all materials before discarding container.

TRANSPORTATION INFORMATION:

DOT: Sodium Dichloro-s-triazinetrione

Oxidizer UN2465